



FloorSource

# Scuba Underlayment



- Roll Size: 100 sq ft
- Thickness: 3mm
- Color: Black
- Width: 47"
- Weight per roll: 9lbs
- Materials: Neoprene layer, Foam, Film, Tape
- STC TBD
- IIC TBD
- Moisture Barrier
- Resistant to the growth of bacteria, mildew, and mold
- Sound control
- Installs over all sub-floors, including cement and plywood.



**UL Defender Underlayment** is designed and manufactured with a Neoprene layer, that is the same material wet suits are made from. Attached to the material is a 6 mil vapor barrier to provide extra moisture protection so that a separate moisture barrier is not required. Scuba II has a taped edge resulting in a continuous moisture barrier when the ends and sides are taped together. As well as being highly moisture resistant, Scuba II Underlayment offers outstanding sound deadening qualities. Compared to the 2mm thickness of other underlayment's, the 3mm neoprene of Scuba II Underlayment offers a softer and quieter walking experience.

## INSTALLATION:

1. Roll out underlayment.
2. On the second roll, remove pressure sensitive tape and overlap the plastic, careful not to overlap foam and press tape into lip to create a continuous moisture barrier. The unfinished-smooth side should face down, with the film side facing up.
3. To ensure moisture barrier, end seams must be taped.